

Technical Specification on further interoperability with C

John Reid, ISO Fortran Convener

Fortran 2003 (or 2008) provides for interoperability of procedures with non-optional arguments that are scalars, explicit-shape arrays, or assumed-size arrays, but not with arguments that are assumed-shape, allocatable, pointer, or optional.

We summarize the present draft of a Technical Specification that is intended to fill this gap and allow C functions to accept arguments of any rank or any type and report on its recent ballot.

BCS Fortran Specialist Group
London, 29 September 2011.

C descriptor

A C descriptor for an object is a struct of the type `CFI_cdesc_t`. This type has components:

`base_addr` C address of the first element of the object. NULL if unallocated or not associated.

`elem_len` The `sizeof()` of an element of the object.

`rank` Rank of the object.

`type` Code (see slide on macros) for the type of the object.

`attribute` Code (see slide on macros) to indicate whether the object is allocatable, a pointer, assumed-shape, or otherwise.

`dim[]` Lower bounds, extents, and stride multipliers.

C header file

The C header file `ISO_Fortran_binding.h` provides the C programmer with standardized C structs, macro definitions, and C prototypes for C functions to allow access in C to additional Fortran features.

Type for bounds and strides

The struct type `CFI_dim_t` has components:

`lower_bound` Lower bound of an array in a given dimension.

`extent` Extent of an array in a given dimension.

`sm` Stride multiplier (distance in bytes between successive elements) in a given dimension.

The new calling mechanism

A dummy argument in a Fortran interface that is allocatable, assumed-shape, or a pointer may correspond to a formal parameter in a C prototype that is a pointer to a C descriptor.

When calling the C function from Fortran, a suitable C descriptor is provided by the system.

Assumed-rank object

A dummy argument in an interface may be of assumed rank. E.g.

```
interface
  subroutine scale(a)
    real a(..)
  end subroutine scale
end interface
```

It may correspond to a pointer to a C descriptor in a C function prototype.

Allows a C function to accept an allocatable, assumed-shape, or a pointer array of any rank.

Severely restricted in Fortran. Can be passed around, remaining as assumed rank, or passed as the first argument to an inquiry function.

5

Assumed-type objects

A dummy argument may be of assumed type. E.g. interface

```
subroutine archive(a)
  type(*) a
end subroutine archive
end interface
```

Allows a C function to accept an allocatable, assumed-shape, or a pointer array of any type.

If it is not allocatable, assumed-shape, assumed-rank, or a pointer, it may correspond to a pointer to void in a C function prototype.

Allows a C function to accept a Fortran object of any type. Helpful for calling MPI.

Severely restricted in Fortran. Can be passed around, remaining as assumed type, or passed as the first argument to some inquiry functions.

6

Optional arguments

An absent actual argument in a reference is indicated by a formal parameter with the value NULL.

7

Macros

CFI_MAX_RANK : Largest rank supported.

Attribute codes:

CFI_attribute_assumed : assumed-shape

CFI_attribute_allocatable : allocatable

CFI_attribute_pointer : pointer

CFI_attribute_unknown_size : assumed size

Type codes:

CFI_type_struct : interoperable struct

CFI_type_signed_char : signed char

CFI_type_short : short

CFI_type_int : int

CFI_type_float : float

CFI_type_double : double

CFI_type_cptr : void *

CFI_type_cfunptr : pointer to a function

... Lots more types.

8

Constructing C descriptors in C

Important changes have been made in the last year for the sake of safety when Fortran is called from C.

A C descriptor must not be initialized, updated, or copied other than by calling one of these functions.

`CFI_allocate` does a Fortran allocation

`CFI_deallocate` does a Fortran deallocation

`CFI_establish` establishes a C descriptor

`CFI_section` updates a C descriptor to describe an ordinary array section

`CFI_select_part` updates a C descriptor to describe an array section such as `array%part`

`CFI_setpointer` updates a C descriptor to point to the whole of an object or be disassociated.

No mixing of C and Fortran allocation mechanisms is allowed.

9

Other functions

`CFI_address` computes the C address of an object described by a C descriptor

`CFI_is contiguous` tests the contiguity of an array described by a C descriptor

10

The DTR ballot

The ballot has just finished and the result was

12 Approval as presented

1 Approval with comments (Germany)

1 Disapproval (UK)

5 Abstentions

The comments are not very severe and I expect the TS to complete next year.

11